



- FEATURES:**
- Provides external wall support and eliminates the need to install internal wall backing.\*\*
  - Can be centered on the wall regardless of stud location
  - Patented open design allows cooling by in-room HVAC so no need for active cooling system.
  - The Chief TS218SU articulating mount allows for tech to access equipment for servicing behind the display.
  - 49"+ Slim can achieve ADA requirements of 4" (10.16cm) depth with the use of certain displays and is intended for use in egress pathways and with no furniture under the display.

SPECIFICATIONS	
DIMENSIONS	42.44"X 24.88" X 2.00" (1077.91mm X 631.83 X 50.80)
NUMBER OF RACK UNITS	0
WEIGHT	29 LB (13.2 KG)
MIN # OF STUDS REQUIRED	2
DISPLAY SIZE COMPATIBILITY	49"- 65" (1m 24cm - 1m 65cm)
DISPLAY WEIGHT LIMIT	125 LB (56.7 KG)
ADDITIONAL MOUNT REQUIRED	PEERLESS SUA771PU
MATERIAL	12-GAUGE STEEL
FINISH	MATTE BLACK POWDER COAT
MFR PART #	SET-49-SLIM-P
WESCO #	10587532
ADA COMPLIANT	YES*

\*WITH THE USE OF CERTAIN DISPLAYS.  
\*\*WITH APPROVAL FROM SITE'S STRUCTURAL ENGINEER.

ROOMREADY SET - 49"+ SLIM DIMENSIONAL DRAWINGS

