



- FEATURES:**
- Provides external wall support and eliminates the need to install internal wall backing.**
 - Can be centered on the wall regardless of stud location
 - Patented open design allows cooling by in-room HVAC so no need for active cooling system.
 - Additional articulated mounts extend out for tech to access equipment for servicing.
 - 65"+ Slim can achieve ADA requirements of 4" (10.16cm) depth with the use of certain displays and is intended for use in egress pathways and with no furniture under the display.

SPECIFICATIONS	
DIMENSIONS	56.38" X 31.25" X 2.50" (1431.93mm X 793.75 X 63.50)
NUMBER OF RACK UNITS	0
WEIGHT	49 LB (22.2 KG)
MIN # OF STUDS REQUIRED	3
DISPLAY SIZE COMPATIBILITY	65"-84" 1m 63cm-2m 11cm
DISPLAY WEIGHT LIMIT	125 LB (56.7 KG)
ADDITIONAL MOUNT REQUIRED	PEERLESS SUA771PU
MATERIAL	12-GAUGE STEEL
FINISH	MATTE BLACK POWDER COAT
MFR PART #	SET-65-SLIM-P
WESCO #	10587534
ADA COMPLIANT	YES*

*WITH THE USE OF CERTAIN DISPLAYS.
**WITH APPROVAL FROM SITE'S STRUCTURAL ENGINEER.

ROOMREADY SET - 65"+ SLIM DIMENSIONAL DRAWINGS

